

Product Data Sheet

TECHFORM Sakor

Description:

Aerosol preservative TECHFORM Sakor is a carefully selected mixture of oils with anticorrosive and antioxidant additions. It is used mainly for maintenance of injection form and others metal tools that used in processing of plastics. Creates an oil protective film protecting against moisture and corrosion.

Advantages:

- Easy to use. By inserting a yellow marker, the protected surface is visible.
- Effective in small amounts
- Leaves an oil film.
- Self-recoverable after several injections.
- Repels water

The fields of application:

- Machine and equipment maintenance.
- Maintenance of mold working surfaces during renovations.
- Temporary protection of injection molds and other processing tools during storage and transport.

Properties:

- Form: aerosol, yellow
- Odour: characteristic
- Density: 0,7 g/cm³
- (In)flammability: inflammable.
- Solubility: in solvents, not in water.

Packaging:

- Aerosol 400 ml, 20 pc. in carton



Directions for use:

In order to obtain a thin and even layer, apply the spray on a clean and degreased surface, spraying it from a distance of 25 to 30 cm. The operations can be repeated after evaporation of the solvent from the previously applied layer.

Guidance for users:

The product contains flammable liquids and gases. During application, the room should be well ventilated. Do not spray an open flame. Protect against ignition source. Keep away from children. Store at temperatures below 50°C, away from sources of heat and direct sunlight. Before use, read the product safety data sheet.

Warning

The product is intended for industrial use only. The information contained in the card presents the current state of knowledge and experience. The information provided can not be used as a substitute for the necessary tests, which alone can ensure the user that this product for it is purposes. It is the user who is responsible for compliance with applicable legal provisions. Please, make sure that the user in possession of the latest version of the MSDS.