

# SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

## Techform Asilen 12

Creation date 09th January 2024  
Revision date Version 3.1

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. Product identifier**  
Substance / mixture Techform Asilen 12  
mixture  
UFI SPWT-29AC-M00F-CEQE
- 1.2. Relevant identified uses of the substance or mixture and uses advised against**  
**Mixture's intended use**  
Release agent, antiadhesive, lubricant  
**Main intended use**  
PC-TEC-11 Lubricants, greases, release agents  
**Secondary uses**  
PC-TEC-17 Processing aids  
**Mixture uses advised against**  
The product should not be used in ways other than those referred in Section 1.
- 1.3. Details of the supplier of the safety data sheet**  
**Manufacturer**  
Name or trade name Techplast Sp. z o.o.  
Address Ciepłownicza 8, Rzeszów, 35-959  
Poland  
VAT Reg No PL8132993396  
Phone +48178642016  
E-mail b.sarna@techform.pl  
Web address www.techform.pl
- Supplier**  
Name or trade name Techplast Sp. z o.o.  
Address Ciepłownicza 8, Rzeszów, 35-959  
Poland  
VAT Reg No PL8132993396  
Phone +48178642016  
E-mail b.sarna@techform.pl  
Web address www.techform.pl
- Competent person responsible for the safety data sheet**  
Name Techplast Sp. z o.o.  
E-mail b.sarna@techform.pl
- 1.4. Emergency telephone number**  
European emergency number: 112

### SECTION 2: Hazards identification

- 2.1. Classification of the substance or mixture**  
**Classification of the mixture in accordance with Regulation (EC) No 1272/2008**

The mixture is classified as dangerous.

Aerosol 1, H229, H222  
Asp. Tox. 1, H304  
Skin Irrit. 2, H315  
STOT SE 3, H336  
Repr. 2, H361  
STOT RE 2, H373  
Aquatic Chronic 2, H411

**Most serious adverse physico-chemical effects**

Extremely flammable aerosol. Pressurised container: May burst if heated.

**Most serious adverse effects on human health and the environment**

May cause damage to organs through prolonged or repeated exposure. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. Causes skin irritation. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects.

# SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

## Techform Asilen 12

Creation date 09th January 2024  
Revision date Version 3.1

### 2.2. Label elements

#### Hazard pictogram



#### Signal word

Danger

#### Hazardous substances

Węglowodory, C6-C7, n-alkany, izoalkany, cykliczne, >5% n-heksanu

#### Hazard statements

H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.  
H361 Suspected of damaging fertility or the unborn child.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H411 Toxic to aquatic life with long lasting effects.

#### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P280 Wear protective gloves.  
P391 Collect spillage.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

### 2.3. Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Chemical characterization

Mixture of substances and non-hazardous additives specified below.

**Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment**

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
Index: 601-004-00-0 CAS: 106-97-8 EC: 203-448-7	butane	<40	Flam. Gas 1, H220 Press. Gas (compressed gas), H280	1, 2
EC: 924-168-8 Registration number: 01-2119475133-43- 0011	Węglowodory, C6-C7, n-alkany, izoalkany, cykliczne, >5% n-heksanu	≤30	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Repr. 2, H361 STOT RE 2, H373 Aquatic Chronic 2, H411	3
Index: 601-003-00-5 CAS: 74-98-6 EC: 200-827-9	propane	<30	Flam. Gas 1, H220 Press. Gas (compressed gas), H280	2

# SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

## Techform Asilen 12

Creation date	09th January 2024	Version	3.1
Revision date			

### Notes

- Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
- Note U (Table 3): When put on the market gases have to be classified as "Gases under pressure", in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned:

Press. Gas (Comp.)  
Press. Gas (Liq.)  
Press. Gas (Ref. Liq.)  
Press. Gas (Diss.)

Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).

- Substance of unknown or variable composition, complex reaction products or biological materials - UVCB.

Full text of all classifications and hazard statements is given in the section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

Do not perform artificial respiration without self-protection (e.g. a mask). If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet.

#### If inhaled

Take care of your own safety, do not let the affected person walk! Terminate the exposure immediately; move the affected person to fresh air. Beware of the contaminated clothes. Depending on the situation, call the medical rescue service and ensure medical treatment considering the frequent need of further observation for at least 24 hours.

#### If on skin

Remove contaminated clothes. Wash the affected area with plenty of water, lukewarm if possible.

#### If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. Rinsing should continue at least for 10 minutes. Provide medical treatment, specialized if possible.

#### If swallowed

If the affected person vomits, make sure to prevent inhalation of the vomit (as there is a danger of lung damage after inhalation of these liquids in the airways also in infinitesimal amount). Provide medical treatment considering the frequent need of further observation for at least 24 hours. Bring an original container with the label and the Safety Data Sheet of the given substance as appropriate.

### 4.2. Most important symptoms and effects, both acute and delayed

#### If inhaled

Cough, headache. May cause drowsiness or dizziness.

#### If on skin

Causes skin irritation.

#### If in eyes

When intruding eyes, it can evoke irritation.

#### If swallowed

Irritation, nausea.

### 4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

#### More information

Other relevant information is not available.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

#### Unsuitable extinguishing media

Water - full jet.

# SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

## Techform Asilen 12

Creation date 09th January 2024  
Revision date Version 3.1

### 5.2. Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

### 5.3. Advice for firefighters

Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Closed containers with the product near the fire should be cooled with water. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Provide sufficient ventilation. Extremely flammable aerosol. Pressurised container: May burst if heated. Remove all ignition sources. Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Do not inhale gases and vapours. Prevent contact with skin and eyes.

### 6.2. Environmental precautions

Do not allow to enter drains. Prevent contamination of the soil and entering surface or ground water.

### 6.3. Methods and material for containment and cleaning up

Ventilate the room. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water.

### 6.4. Reference to other sections

See the Section 8 and 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Prevent formation of gases and vapours in flammable or explosive concentrations and concentrations exceeding the occupational exposure limits. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. Use non-sparking tools. Use of antistatic clothes and footwear is recommended. Do not inhale gases and vapours. Prevent contact with skin and eyes. No smoking. Protect against direct sunlight. Obtain special instructions before use. Do not pierce or burn, even after use. Wash hands and exposed parts of the body thoroughly after handling. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection. Avoid release to the environment.

### 7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Store locked up. Protect from sunlight. Keep container tightly closed. Do not expose to temperatures exceeding 50 °C.

Content	Packaging type	Material of package
400 ml	aerosol can	FE

### The specific requirements or rules relating to the substance/mixture

Solvent vapours are heavier than air and accumulate especially near the floor where they may form an explosive mixture with the air.

### 7.3. Specific end use(s)

Release agent, antiadhesive, lubricant

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

The mixture contains substances for which occupational exposure limits are set.

#### DNEL

Węglowodory, C6-C7, n-alkany, izoalkany, cykliczne, >5% n-heksanu					
Workers / consumers	Route of exposure	Value	Effect	Value determination	Source
Workers	Inhalation	145 mg/m <sup>3</sup>	Chronic effects local		
Workers	Dermal	21 mg/kg/24h	Chronic effects local		
Consumers	Inhalation	27 mg/m <sup>3</sup>	Chronic effects local		

# SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

## Techform Asilen 12

Creation date 09th January 2024  
Revision date Version 3.1

Węglowodory, C6-C7, n-alkany, izaalkany, cykliczne, >5% n-heksanu					
Workers / consumers	Route of exposure	Value	Effect	Value determination	Source
Consumers	Oral	8 mg/kg/24h	Chronic effects local		
Consumers	Dermal	9 mg/kg/24h	Chronic effects local		

### 8.2. Exposure controls

Follow the usual measures intended for health protection at work and especially for good ventilation. This can be achieved only by local suction or efficient general ventilation. If exposure limits cannot be observed in this mode, suitable protection of airways must be used. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

#### Eye/face protection

In case of splash use safety glasses. EN166 - Personal Eye Protection Standard.

#### Skin protection

Hand protection: Protective gloves resistant to the product. Wear protective gloves that are impermeable and resistant to the product (e.g. neoprene, nitrile). It is recommended to change the gloves regularly and replace them immediately if they show any signs of wear, damage (tearing, holes) or changes in appearance (color, elasticity, shape). The selection of the permeation resistance class depends on the time of exposure to the factor and should be selected in accordance with the EN 374 standard. The thickness of the glove layer is determined by the manufacturer based on the permeation exposure class. Penetration time of the glove material: the exact breakthrough time must be obtained from the glove manufacturer and must be observed. Protective nitrile gloves: glove layer thickness at least: 0.34 mm Neoprene protective gloves: in case of contact with a stream of sprayed liquid, protection is recommended at least according to the protection index class 2, in accordance with the penetration time above 30 min. (EN 374). Glove layer thickness: at least: 0.75 mm. In the case of prolonged and intensive contact, protection according to the protection index class 6 is recommended, with a penetration time of over 480 minutes (EN 374). Glove layer thickness: at least: 1.35 mm. Other protection: protective workwear. Contaminated skin should be washed thoroughly.

#### Respiratory protection

In case of inadequate ventilation wear respiratory protection. Under regular circumstances it is not necessary.

#### Thermal hazard

Data not available.

#### Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2. Collect spillage.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	gas
Colour	colourless
Odour	characteristic
Melting point/freezing point	data not available
Boiling point or initial boiling point and boiling range	64 °C (Początkowa temperatura wrzenia składnika mieszaniny o najniższej wartości)
Flammability	Extremely flammable aerosol.
Lower and upper explosion limit	data not available
Flash point	-35 °C (Temperatura zapłonu składnika mieszaniny (rozpuszczalnika) o najniższym punkcie zapłonu)
Auto-ignition temperature	data not available
Decomposition temperature	data not available
pH	non-soluble (in water)
Kinematic viscosity	data not available
Solubility in water	insoluble
Solubility in fats	data not available
Partition coefficient n-octanol/water (log value)	data not available
Vapour pressure	data not available
Density and/or relative density	

# SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

## Techform Asilen 12

Creation date 09th January 2024  
Revision date Version 3.1

Density 0.7 g/cm<sup>3</sup>  
Relative vapour density data not available  
Particle characteristics data not available  
Form spray  
**9.2. Other information**  
Evaporation rate non-applicable  
Explosive properties Vapours mixed up with air can be explosive.

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

The mixture is extremely flammable.

#### 10.2. Chemical stability

The product is stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

Unknown.

#### 10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost. Pressurised container: May burst if heated.

#### 10.5. Incompatible materials

Protect against strong acids, bases and oxidizing agents.

#### 10.6. Hazardous decomposition products

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire.

### SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Inhalation of solvent vapors above values exceeding exposure limits for working environment may result in acute inhalation poisoning, depending on the level of concentration and exposure time. No toxicological data is available for the mixture.

#### Acute toxicity

not available

Węglowodory, C6-C7, n-alkany, izaalkany, cykliczne, >5% n-heksanu					
Route of exposure	Parameter	Value	Exposure time	Species	Sex
Oral	LD <sub>50</sub>	>5840 mg/kg		Rat (Rattus norvegicus)	
Skin	LD <sub>50</sub>	>2920 mg/kg		Rat (Rattus norvegicus)	
Inhalation	LC <sub>50</sub>	>25200 mg/m <sup>3</sup>	4 hours	Rat (Rattus norvegicus)	

#### Skin corrosion/irritation

Causes skin irritation.

Węglowodory, C6-C7, n-alkany, izaalkany, cykliczne, >5% n-heksanu			
Route of exposure	Result	Exposure time	Species
	Drying and cracking of the skin		

#### Serious eye damage/irritation

Based on available data the classification criteria are not met.

# SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

## Techform Asilen 12

Creation date 09th January 2024  
Revision date Version 3.1

### Respiratory or skin sensitisation

Based on available data the classification criteria are not met.

### Germ cell mutagenicity

Based on available data the classification criteria are not met.

### Carcinogenicity

Based on available data the classification criteria are not met.

### Reproductive toxicity

Suspected of damaging fertility or the unborn child.

### Toxicity for specific target organ - single exposure

May cause drowsiness or dizziness.

Węglowodory, C6-C7, n-alkany, izaalkany, cykliczne, >5% n-heksanu					
Route of exposure	Parameter	Value	Result	Species	Sex
Inhalation			Dizziness		

### Toxicity for specific target organ - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

### Aspiration hazard

May be fatal if swallowed and enters airways.

## 11.2. Information on other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

## SECTION 12: Ecological information

### 12.1. Toxicity

Toxic to aquatic life with long lasting effects.

#### Acute toxicity

Węglowodory, C6-C7, n-alkany, izaalkany, cykliczne, >5% n-heksanu				
Parameter	Value	Exposure time	Species	Environment
NOEC	0.17 mg/l	21 days	Aquatic microorganisms (Daphnia magna)	Fresh water
LL <sub>50</sub>	11.4 mg/l	96 hours	Fish (Oncorhynchus mykiss)	
EL <sub>50</sub>	3-22 mg/l	48 hours	Aquatic microorganisms (Daphnia magna)	
EL <sub>50</sub>	35.29 mg/l	48 hours	Aquatic microorganisms (Tetrahymena pyriformis)	
NOEL	2.028 mg/l	28 days	Fish (Oncorhynchus mykiss)	

### 12.2. Persistence and degradability

not available

### 12.3. Bioaccumulative potential

Data not available.

### 12.4. Mobility in soil

Data not available.

### 12.5. Results of PBT and vPvB assessment

# SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

## Techform Asilen 12

Creation date 09th January 2024  
Revision date Version 3.1

Product does not contain any substance meeting the criteria for PBT or vPvB in accordance with the Annex XIII of Regulation (EC) No 1907/2006 (REACH) as amended.

### 12.6. Endocrine disrupting properties

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

### 12.7. Other adverse effects

Data not available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Proceed in accordance with valid regulations on waste disposal. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Empty containers may be used at waste incinerators to produce energy or deposited in a dump with appropriate classification. Perfectly cleaned containers can be submitted for recycling.

#### Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

#### Waste type code

07 01 04\* other organic solvents, washing liquids and mother liquors

#### Packaging waste type code

15 01 11\* metallic packaging containing a hazardous solid porous matrix (for example asbestos), including empty pressure containers

15 01 04 metallic packaging

(\* ) - Hazardous waste according to Directive 2008/98/EC on hazardous waste

## SECTION 14: Transport information

### 14.1. UN number or ID number

UN 1950

### 14.2. UN proper shipping name

AEROSOLS

### 14.3. Transport hazard class(es)

2 Gases

### 14.4. Packing group

II

### 14.5. Environmental hazards

Toxic to aquatic organisms.

### 14.6. Special precautions for user

Reference in the Sections 4 to 8. Make sure that the person transporting the product knows the ways of handling the product in the event of accident.

### 14.7. Maritime transport in bulk according to IMO instruments

It is not intended for transport in bulk


#### Additional information

Hazard identification No.

UN number

Classification code

Safety signs



5F

2.1+dangerous for the environment



# SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

## Techform Asilen 12

Creation date	09th January 2024	Version	3.1
Revision date			

Tunnel restriction code (D)

### Air transport - ICAO/IATA

Packaging instructions passenger 203

Cargo packaging instructions 203

### Marine transport - IMDG

EmS (emergency plan) F-D, S-U

MFAG 620

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

### 15.2. Chemical safety assessment

There was no evaluation.

## SECTION 16: Other information

### A list of standard risk phrases used in the safety data sheet

H220 Extremely flammable gas.  
H222 Extremely flammable aerosol.  
H225 Highly flammable liquid and vapour.  
H229 Pressurised container: May burst if heated.  
H280 Contains gas under pressure; may explode if heated.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.  
H361 Suspected of damaging fertility or the unborn child.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H411 Toxic to aquatic life with long lasting effects.

### Guidelines for safe handling used in the safety data sheet

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P280 Wear protective gloves.  
P391 Collect spillage.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

### Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

### Key to abbreviations and acronyms used in the safety data sheet

ADR European agreement concerning the international carriage of dangerous goods by road  
BCF Bioconcentration Factor  
CAS Chemical Abstracts Service  
CLP Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures  
EC Identification code for each substance listed in EINECS  
EINECS European Inventory of Existing Commercial Chemical Substances  
EL<sub>50</sub> Effective Loading for 50% of the tested organisms

# SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

## Techform Asilen 12

Creation date	09th January 2024	Version	3.1
Revision date			

EmS	Emergency plan
EU	European Union
EuPCS	European Product Categorisation System
IATA	International Air Transport Association
IBC	International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
INCI	International Nomenclature of Cosmetic Ingredients
ISO	International Organization for Standardization
IUPAC	International Union of Pure and Applied Chemistry
LC <sub>50</sub>	Lethal concentration of a substance in which it can be expected death of 50% of the population
LD <sub>50</sub>	Lethal dose of a substance in which it can be expected death of 50% of the population
LL <sub>50</sub>	Lethal Loading for 50% of tested organisms
log K <sub>ow</sub>	Octanol-water partition coefficient
NOEC	No observed effect concentration
NOEL	No observed effect level
OEL	Occupational Exposure Limits
PBT	Persistent, Bioaccumulative and Toxic
ppm	Parts per million
Press. Gas (Comp.)	Gas under pressure: compressed gas
Press. Gas (Diss.)	Gas under pressure: dissolved gas
Press. Gas (Liq.)	Gas under pressure: liquefied gas
Press. Gas (Ref. Liq.)	Gas under pressure: refrigerated liquefied gas
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Agreement on the transport of dangerous goods by rail
UN	Four-figure identification number of the substance or article taken from the UN Model Regulations
UVCB	Substances of unknown or variable composition, complex reaction products or biological materials
VOC	Volatile organic compounds
vPvB	Very Persistent and very Bioaccumulative
Aerosol	Aerosol
Aquatic Chronic	Hazardous to the aquatic environment (chronic)
Asp. Tox.	Aspiration hazard
Flam. Gas	Flammable gas
Flam. Liq.	Flammable liquid
Press. Gas	Gases under pressure
Repr.	Reproductive toxicity
Skin Irrit.	Skin irritation
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure

### Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

### Recommended restrictions of use

not available

### Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended.  
REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

### The changes (which information has been added, deleted or modified)

# SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

## Techform Asilen 12

Creation date	09th January 2024	Version	3.1
Revision date			

The version 3.1 replaces the SDS version from 10 November 2022. Changes were made in sections 1, 2, 6, 7, 8, 13, 14, 15 and 16.

### More information

Classification procedure - calculation method.

### Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.

TECHFORM